SPORTENZIA

FITTING GUIDE

MEROCA BAR END PLUGS, GOLD

A pair of expanding plugs that close the ends of the handlebar and protect its edges. Fitting, checking the hold and removal.

REF. BO9 · 22 TO 24 MM HANDLEBARS · AL6061 ALLOY AND ABS, M4 BOLT



Before fitting

Each plug is made of an alloy cap, a plastic expander and an M4 × 34 mm hex socket bolt: have a **suitable Allen key** ready. Remove the old plug and check that the end of the bar is clean and free of burrs.

Fitting

1. **Loosen the bolt** a few turns: the expander stays slim and slides in without forcing.
2. **Push the plug in** to the end of the bar until the cap sits flush. On a road bar, it also holds the end of the bar tape.
3. **Tighten the bolt** clockwise: the expander spreads and locks against the inside of the bar. Tighten firmly, without forcing.
4. **Check** by pulling and twisting the plug by hand: it must neither move nor come out. Fit the second one the same way.

Removal

Loosen the bolt a few turns to release the expander, then pull the plug out of the bar.



Alloy cap, plastic expander and M4 × 34 mm bolt.

Specifications

Handlebars	**22 to 24 mm (road, gravel, MTB)**	Bolts	**M4 × 34 mm, included**
Material	**AL6061 alloy, ABS**	Weight	**19 g per pair**
Colour	**Gold**	Contents	**2 plugs**

SAFETY

- Do not ride with an open bar end: in a fall, a bare tube end can cause injury.
- A plug that turns or works loose: tighten it before riding on.
- Check the hold after a fall or after transport.

Need help?

sportenzia.com/pages/contact

Our team answers your questions about fitting.