VELKYNE

USER GUIDE

# WAHOO ELEMNT BOLT V2 PACK: CASE AND GLASS

Moulded black silicone case and oleophobic 0.5 mm tempered glass for the Wahoo ELEMNT Bolt V2. Glass first, case second: this guide covers the order, the fitting and the care.

**WAHOO ELEMNT BOLT V2** · TEMPERED GLASS 0.5 MM · BLACK SILICONE CASE



01 · CONTENTS

## PACK CONTENTS AND FITTING THE GLASS

### In the pack

| ITEM | QTY | DETAILS |
|---|---|---|
| Silicone case | 1 | Black, moulded for the Bolt V2; buttons and charging port free |
| Tempered glass | 1 | 0.5 mm, oleophobic coating, almost invisible once fitted |

### Fitting the glass

1. **Clean the screen** with alcohol or the damp wipe, dry it with the microfibre, dab it with the tape. Check against the light: no smear, no speck.
2. **Dry-fit the glass** with its film on: it covers the screen without riding onto the frame or getting in the way of the buttons. Note this position.
3. **Peel the film** off the adhesive side, holding the glass by its edges. Do not touch the sticky side again.
4. **Lay one edge** on the mark and let the glass settle: adhesion spreads on its own within seconds.
5. **Push the air out** from the centre to the edges with the microfibre. Any remaining micro-bubbles clear within 24 h.

FITTING ORDER

- **1. The glass**, on a bare, clean screen: this is the step that is hard to redo.
- **2. The case**, whose rim covers the outline of the glass and holds it.
- **3. The computer** clipped onto its mount, case on.

### Before fitting

- A room with **no dust in the air** and no draught; clean hands, computer switched off, screen dry.
- Something to clean with: a damp wipe or alcohol, a microfibre cloth, adhesive tape to trap dust.
- Computer **off its mount**: the case slips over the bare unit.

### Compatibility

| | | | |
|---|---|---|---|
| Computer | **Wahoo ELEMNT Bolt V2** | Does not fit | **First-gen Bolt, Roam** |
| Glass | **0.5 mm, oleophobic** | Case | **Black silicone** |
| Kept free | **Buttons, charging, mount** | | |

02 · FITTING

# CASE, CARE, TROUBLESHOOTING

## Slipping the case on

1. **Slip the case on** over one end of the computer, then fold it over the other: its rim covers the outline of the glass without lifting it.
2. **Seat every button** in its cut-out; the charging port and the mounting tabs on the back must stay clear.
3. **Clip the computer** onto its mount, case on: it must lock as it does bare, a quarter turn until it clicks.

## If something goes wrong

| SYMPTOM | LIKELY CAUSE | FIX |
|---|---|---|
| White dot with a halo | Dust trapped during fitting | Lift the edge with the tape, pick it off, lay it back down |
| Stubborn bubble after 24 h | Dust or a greasy smear underneath | Same remedy; clean if the smear comes back |
| Case lifting an edge of the glass | Glass off-centre | Refit it before slipping the case on |
| Computer will not lock | Case not seated, or tabs not lined up | Clear the mount cut-out, line up, turn until it clicks |

## Taking the case off

To clean the computer or change the glass, peel the case off gently from one corner of the housing, never by pulling on a button cut-out: that is where a case tears.

## Care

- Case: rinse it in clean water after a muddy ride, dry it before putting it back. No solvent.
- Glass: clean with the microfibre. A glass cracked by an impact has done its job: replace it.

**BEFORE YOU RIDE**

- Computer locked on its mount: it neither turns nor lifts.
- Buttons responding through the case, charging port accessible.
- Glass with no bubble and no lifted edge.

**DON'T**

- No glass on a cracked screen, no case slipped on before the glass.
- Do not pull the computer upward to remove it: a quarter turn the other way.

## On video

Independent tutorial on fitting a screen protector, scan to watch.

**How to install ANY screen protector perfectly, 10 steps**
MobileReviewsEh · English

## Need help?

**velkyne.com/contact**
Our team answers your questions about fitting, mounting and compatibility.

© 2026 Velkyne. All rights reserved.