VELKYNE

FITTING GUIDE

WAHOO ELEMNT ROAM 2 PACK

Oleophobic 0.5 mm tempered glass and a moulded black silicone case. Glass first, case second: the case holds the glass by its edges.

WAHOO ELEMNT ROAM 2 · TEMPERED GLASS 0.5 MM · BLACK SILICONE CASE



Before fitting

- A room with **no dust in the air** and no draught; clean hands, computer switched off, screen dry.
- Something to clean with: a damp wipe or alcohol, a microfibre cloth, adhesive tape or a dust-removal sticker.
- Computer **off its mount**: the case slips over the bare unit.

The glass, then the case

1. **Clean the screen** with alcohol or the damp wipe, dry it with the microfibre, then dab it with the tape. Check against the light.
2. **Dry-fit the glass** with its film on: it covers the screen without riding onto the frame or getting in the way of the buttons. Note this position.
3. **Peel the film** off the adhesive side, holding the glass by its edges, line one edge up on the mark and let the glass settle.
4. **Push the air out** from the centre to the edges with a soft card. Any remaining micro-bubbles clear within 24 to 48 h.
5. **Slip the case on** over one end of the computer, then fold it over the other: its rim covers the outline of the glass. Check that every button sits in its cut-out.
6. **Check the openings:** buttons, charging port and rear mount must be free. Clip the computer onto its Wahoo mount with the case on.

Specifications

Compatibility	**ELEMNT Roam 2**	Does not fit	**First-gen Roam**
Contents	**Case + glass**	Case	**Black silicone**
Glass	**0.5 mm, oleophobic**	Kept free	**Buttons, charging, mount**

IF SOMETHING GOES WRONG

- **Dust under the glass** (white dot with a halo): lift the nearest corner with the tape, pick the particle off, lay it back down.
- **Misaligned glass**: lift it off entirely right away and start again from step 2.
- **Case lifting an edge of the glass**: the glass is off-centre, refit it before slipping the case on.

DON'T

- No glass on a cracked screen, no case slipped on before the glass. A glass cracked by an impact has done its job: replace it.

On video

Independent tutorial, scan to watch.

How to install ANY screen protector perfectly, 10 steps
MobileReviewsEh · English

Need help?

velkyne.com/contact
Our team answers your questions about fitting and compatibility.

© 2026 Velkyne. All rights reserved.